

CAB INSTALLATION INSTRUCTIONS

JOHN DEERE 4000 SERIES (4500/4600/4700) (4510/4610/4710) (4120/4320/4520/4720) HARD SIDED CAB ENCLOSURE (p/n: 1JD4120AS) SOFT SIDED CAB ENCLOSURE (p/n: 1JD4120SS)

> The contents of this envelope are the property of the owner. Be sure to leave with the owner when installation is complete.



WARNING This Curtis Cab is designed and manufactured for use only as reasonable weather protection. This cab is not appli-cable, Nor should the cab be considered as protection against roll over, collision or other accidents that may result. This cab is NOT a R.O.P.S. cab. Extreme care should be taken when operating and by qualified, experienced operators only.

WARNING Exposure to Carbon Monoxide can Cause illness, serious injury or death. Never

operate vehicle if suspicious of Carbon Monoxide, Inspect exhaust system for leaks monthly, Leaks can result from loose connections, corrosion, cracks or other damage to the exhaust manifold. If leaks are found, repair or replace exhaust system. Do not use vehicle until repair or replacement is



Curtis Cabs, blades and general accessories add additional weight to the base vehicle. All Curtis accessory weights are listed in product brochures. Deduct the accessories total weight from the vehicles rated capacity and never exceed the vehicles rated capacity including driver and passenger.

Rev. T, p. 1 of 11







